



J-V(ZN)H 2F ORG

CONSTRUCTION

- Fibre** (uncoloured) : SM 9/125; MM 50/125; MM 62,5/125
- Buffer** : tight (24T1) - stripability up to 10 cm
semi-tight (24S1) - stripability 20 to 100 cm
- Material** : LSZH
- Colour code** : 1st: natural, 2nd: blue
Other buffer colours available on request.
- Strength member** : Aramid yarn
- Rip-cord** : none
- Outer jacket** : LSZH
- Colour** : SM 9/125 - Yellow
MM 50/125 - Green
MM 62,5/125 - Orange
Other jacket colours available on request

Identification marking

- Print colour** : black
- Print method** : ink jet
- Standard legend** : manufacturer's name, job number, type of cable, length marking @ 1 m intervals
Custom print legends available on request.

0	15.10.2007		<p>J-V(ZN)H 2f Indoor Duplex Cable</p>	
			<p>24T1.0 24S1.0</p>	<p>Page 1/2</p>

FIBRE SPECIFICATION

Fibre Type (fibre order code)	Multimode Fibres						Dimensions			
	Optical Performance						Numerical Aperture (um)	Core Diameter (um)	Cladding Diameter (um)	Coating Diameter (um)
	Attenuation (typical / maximum) (dB/km)	Bandwidth (overfilled launch) (MHz.km)		1Gbps Ethernet Transmission Link Length						
	850 nm	1300 nm	850 nm	1300 nm	850 nm	1300 nm				
Multimode 62.5/125 OM1 (G6)	2.8/3.3	0.7/1.2	220	600	300	550	0.275 ± 0.015	62.5 ± 2.5	125 ± 1.0	245 ± 10
Multimode 50/125 OM2 (G5)	2.5/3.2	0.7/1.0	500	800	550	550	0.20 ± 0.015	50 ± 2.5	125 ± 1.0	245 ± 10
Multimode 50/125 OM2 (M5)	2.3/2.8	0.6/0.9	600	1200	600	600	0.20 ± 0.015	50 ± 2.5	125 ± 1.0	245 ± 10
Multimode 50/125 OM2 (N5)	2.3/2.8	0.6/0.9	600	1200	750	2000	0.20 ± 0.015	50 ± 2.5	125 ± 1.0	245 ± 10
Multimode 50/125 10GBE OM3 (X5)	-/3.2	-/1.1	1500	500	300 ^A	-	0.20 ± 0.015	50 ± 2.5	125 ± 1.0	245 ± 10
Multimode 50/125 10GBE OM3 (Y5)	-/3.2	-/1.1	3500	500	550 ^A	-	0.20 ± 0.015	50 ± 2.5	125 ± 1.0	245 ± 10

Note A - 10 Gbps Ethernet

Fibre Type (fibre order code)	Singlemode Fibres					Dimensions				
	Optical Performance					Cable Cut-Off Wavelength (nm)	Mode Field Diameter (um)		Cladding Diameter (um)	Coating Diameter (um)
	Attenuation (typical / maximum) (dB/km)	Chromatic Dispersion (ps/(nm.km))		Individual fibre PMD (ps/√km)						
	1310 nm	1550 nm	1310 nm	1550 nm		1310 nm	1550 nm			
Singlemode 9/125 G.652D - LWP (S9)	0.33/0.5	0.25/0.4	3.5	18.0	≤ 0.2 ^B	≤ 1260	9.2 ± 0.4	10.4 ± 0.4	125 ± 1.0	245 ± 10
Singlemode 9/125 G.652D - ZWP (E9)	0.32/0.5	0.25/0.4	3.5	18.0	≤ 0.1 ^B	≤ 1260	9.2 ± 0.4	10.4 ± 0.4	125 ± 0.7	245 ± 10
Singlemode 9/125 G.655 (B9)	-	-/0.32	-8.0	2.6 - 6.0 ^C	< 0.1 ^B	≤ 1260	-	8.4 ± 0.6	125 ± 0.7	245 ± 5

Note B - As measured with Low Mode Coupling (LMC) technique in fiber form, value may change when cabled.

Note C - Chromatic dispersion value at 1530 - 1565 nm



ORDER EXAMPLE

2100 m J-V(ZN)H 2E9/125G.652D YEL; cable specification 24T1

MECHANICAL AND ENVIRONMENTAL PROPERTIES

Max. tensile strength (installation)	IEC 60794-1-2/E1A	200 N
Crush resistance	IEC 60794-1-2/E3	1000 N/10cm
Impact resistance	IEC 60794-1-2/E4	3 impacts (w/2N.m)
Minimum bend radius (long term)	IEC 60794-1-2/E11A	10x cable diameter (no load)
Minimum bend radius (short term)	IEC 60794-1-2/E11B	15x cable diameter (load)
Flammability	EN 50266-1&2 (IEC 60332-3-24)	Suitable for indoor use
Acid gases	EN 50267-1&2	Suitable for indoor use
Smoke density	EN 50268-1&2	Suitable for indoor use
Temperature range	IEC 60794-1-2/F1	
installation		-5 °C to + 40 °C
operation		-20 °C to + 50 °C
storage		-25 °C to + 60 °C
Cable size:		
Buffer nominal diameter		0,9 ± 0,05 mm
Simplex nom. diameter		2,4 ± 0,1 mm
Cable width		5,1 ± 0,2 mm
Cable informative nominal weight		12 kg/km
Standard put-up length / Drum size		2100 m / 60x30x42 cm (plywood)

Cable life time - minimum 30 years
This cable is suitable for indoor use only.

0	15.10.2007		<h3>J-V(ZN)H 2f</h3> <h4>Indoor Duplex Cable</h4>		
				Issue <h2 style="margin: 0;">24T1.0</h2> <h2 style="margin: 0;">24S1.0</h2>	Page <h2 style="margin: 0;">2/2</h2>
		Ing. Miroslav Testař Head of control and research	Ing. František Cempírek Head of technology		