


A-DQ(ZN)2Y max. 12F

This cable is suitable for outdoor installation.



Mechanical and Environmental properties

Test	Value	Unit	Method
Cable outer diameter	2,5 ± 0,1	mm	EN 60811-203
Cable weight	5	kg/km	
Outer jacket thickness	0,35	mm	
Loose tube diameter	1,7	mm	
Max. tensile strength	0,5 % fiberstrain	90	N EN 60794-1-21-E1
	0,6 % fiberstrain	105	N
Crush resistance test	700	N	EN 60794-1-21-E3
Impact resistance test	5	Nm	EN 60794-1-21-E4
Min. bend radius (no load)	10	× OD	EN 60794-1-21-E11a
Min. bend radius (load)	15	× OD	EN 60794-1-21-E11b
Temperature range	Installation	-15 to +50	°C
	Operation	-15 to +70	°C
	Storage	-20 to +70	°C

Cable life time - minimum 30 years

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Fibre colour coding

According to IEC 60304

1	Red	7	Brown
2	Green	8	Violet
3	Blue	9	Turquoise
4	Yellow	10	Black
5	White	11	Orange
6	Grey	12	Pink

Other fibre colour sequences available on request

Packing

Depending on ordered put-up lengths

