


J/A-DQ(BN)H(SR)H PH120 max. 24F

This cable is suitable for indoor or outdoor installation. The cable is fire resistant. The cable has full rodent protection.

**Mechanical and Environmental properties**

Test	Value	Unit	Method
Cable outer diameter	12,5 ± 0,4	mm	EN 60811-203
Cable weight	211	kg/km	
Outer jacket thickness	2	mm	
Loose tube diameter	3,2	mm	
Max. tensile strength	2000	N	EN 60794-1-21-E1
Crush resistance test	5000	N	EN 60794-1-21-E3
Impact resistance test	30	Nm	EN 60794-1-21-E4
Min. bend radius (no load)	15	× OD	EN 60794-1-21-E11a
Min. bend radius (load)	20	× OD	EN 60794-1-21-E11b
Moisture resistance test	pass		EN 60794-1-22-F5
Temperature range	Installation	-15 to + 50	°C
	Operation	-30 to + 80	°C
	Storage	-40 to + 80	°C
Circuit integrity	pass		ČSN EN IEC 50200 ČSN EN 50582 PH120
Classification CPR	Classification in accordance with ČSN 13501-6 (EN 13501-6) 1-24F Eca		
Fire properties Flammability	pass		EN 60332-1-2

Cable life time - minimum 30 years

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Fibre colour coding

According to IEC 60304

1	Red	7	Brown	13	Red*	19	Brown*
2	Green	8	Violet	14	Green*	20	Violet*
3	Blue	9	Turquoise	15	Blue*	21	Turquoise*
4	Yellow	10	Black	16	Yellow*	22	Natur*
5	White	11	Orange	17	White*	23	Orange*
6	Grey	12	Pink	18	Grey*	24	Pink*

*with black rings

Other fibre colour sequences available on request

Packing

Depending on ordered put-up lengths

